

# Stainless Steel Code Lock SS-515

Rustfri stål kodelås SS- 515



<b>Door Thickness</b>	35mm - 65 mm
<b>Spindle Type</b>	2-part 8mm spring loaded spindle
<b>Body Material</b>	Stainless Steel
<b>Lock Material</b>	Zink Alloy
<b>Non-Handed</b>	Lock will fit doors hung on the left or right
<b>Mortice Latch</b>	Medium duty tubular mortice latch with 'anti-shim' plunger. Latch retracts by turning inside handle freely, or the outside handle after code input. The CL515 model provides a Code Free option. The outside lever will retract the latch freely until disabled..
<b>Cylinders</b>	None.
<b>Codes</b>	4 – 6 digits gives a total of 463 combinations

# Stainless Steel Code Lock SS-515

## Rustfri stål kodelås SS- 515

The lock is factory set with a randomly selected 5 digit code starting with the C button.  
The code is not recorded by the factory.  
The code can be changed as often as required to any other 5 digit code.  
Every new code must start with the C button.  
Using the spare tumblers, the code length can be changed to 4 or 6 digits.

Neoprene seals are included on both sides to provide friction against the face of the door and to prevent damage from over tightening of the fixing bolts.

The outside lever handle has a slipping clutch to prevent damage to the lock if the handle is forced.

Suitable for internal and external use.

